



US Patent # 8,181,378
©TALON Grips, Inc. All Rights Reserved



MADE IN USA

Five Rules of Firearm Safety:

1. Assume guns are ALWAYS loaded.
2. Never allow the muzzle to cover anything you are not willing to destroy.
3. Keep your trigger finger straight along the frame until you are ready to fire.
4. Be sure of your target, backstop and beyond.
5. Always follow all instructions and warnings applicable to your firearm.

INSTALLATION INSTRUCTIONS

FIELD STRIP TEST FIT

Unload and **FIELD STRIP** the firearm for safety. With the backing still on the TALON Grip, do a **TEST FIT** to ensure you have the correct grip and to understand how the grip fits the firearm. Most grips do not need trimming. However, if cut lines are printed on the back of the grip, they may be used to ensure proper fit of the grip on your firearm. Please contact customer support if you have questions with trimming or fit.

CLEAN

Use ONLY RUBBING ALCOHOL to **CLEAN** the pistol grip area removing any dirt or oil. The firearm must be completely dry before continuing. For improved cleaning use extra rubbing alcohol and a small brush in addition to the supplied alcohol swab.

ALIGN WRAP TUCK

Remove the backing. Starting with the left side, **ALIGN** the TALON Grip with the front and bottom of the factory pistol grip (**A** and **B**), maintaining a consistent reveal around the magwell (some grips have graphic cutouts which may help with proper alignment). **DO NOT STRETCH**, gently **WRAP** the grip on to prevent trapping air. Make sure the grip is properly centered on the backstrap (**C**). Very lightly wrap the finger strip(s) (**D**) evenly around the front of the pistol. **TUCK** any excess material **UNDER** the left side panel (**A**). If the TALON Grip is misaligned, gently peel back the grip, reposition, and reapply as many times as needed.

HEAT PRESS REPEAT

When the TALON Grip is properly aligned **HEAT** it with a hair dryer or heat gun to the temperature of a warm cup of coffee and **PRESS FIRMLY** into place. DO NOT HEAT OVER 130 DEGREES FAHRENHEIT. **REPEAT** this step several times conforming the TALON Grip to the gun's factory grip. Pay special attention to pressing down firmly all outside edges including the backstrap.

TALON Tips:

- **MOST GRIPS REQUIRE NO TRIMMING.** Some grips have cut lines printed on the back to accommodate different versions of the same gun. Contact customer support with any questions.
- **NEVER ALLOW ANY PORTION OF THE GRIP TO COVER THE MAGAZINE RELEASE BUTTON.**
- **GRANULATE TEXTURE:** If a less abrasive feel is desired, sand ONLY THE GRIP with 120 grit sandpaper.
- **RUBBER TEXTURE:** To enhance grip, clean the grip with rubbing alcohol and a soft cloth.

